

LED-6698C



- Feature:
1. sending card can be built-in the IPC.
 2. Dual display, the maximum support HD 1920X1080.
 3. One serial port, one gigabit ethernet ports, support WIFI, 3G and 4G etc wireless networks way.
 4. +12V DC input, wide temperature: -30~70°C .
 5. Compact, easy to install and carry.
 6. CE certificate, have certification , convenient export declaration.

Specifications described in the following table:

CPU	INTEL 1.8G CPU
Internal memory	1 x DDR3 1066/1333MHz DIMM, standard configuration 2G, max support 4GB
display	Dual display, VGA and DVI, support HD
resolution	MAX support 1920*1080
Sending card	LINSN etc, can be built-in
Network card	two gigabit ethernet ports, in addition to support 3G, 4G and WIFI
Memory standard	Standard 320G note book disk or SSD
USB	4pcs USB 2.0 ports
COM port	1pc RS232 COM port
Power port	+12V voltage input
BIOS	AMI authorization 8Mbit BIOS procedure, support RPL/PXE diskless booting
SIZE	330mm(H)×205mm(W)×56mm (D)
Work environment	
Work temperature	-30~70°C
Work humidity	10%~80% relative humidity, without solidification
approve	European union CE

Installation size chart

